

RL5416DC

RICE LAKE DIGITAL CANISTER LOAD CELLS, IN STAINLESS STEEL,
"RL5416DC" SERIES WITH CONNECTORS



Digital canister load cells for CE-M approved weighbridges, tanks, silos, etc. Manufactured in STAINLESS STEEL, IP68 protection degree, 4000 divisions.

Specifically developed for working without junction box.

CAPACITIES: 30 t, 40 t

OIML R60. C4 precision class.

Stainless steel body. **IP68** Protection Degree.

h= 150 mm.

Working in cooperation with:

CHING-HWA SCALE AND WEIGHING SYSTEMS LTD

31-3, LN 26, FUXING RD. 710-YONGKANG DIST - 710 - TAINAN CITY - TAIWAN
Tel. 00886-6-2058115 Fax. 00886-6-2054915
armor@www.ching-hwa.com.tw

The best solution
for advanced industrial
applications

• TECHNICAL FEATURES

METROLOGICAL FEATURES

- Rated capacity: (FS): 30 t, 40 t
- Combined error: 0,02 %F.S
- Creep error (after 30 min.): 0,02 %FS
- Temperature effect on zero: 0,003 %F.S./°C
- Temperature effect on sensitivity: 0,0008 %F.S./°C

OIML R60

- $V_{min} = E_{max}/18000$
- Accuracy class: C4
- Max. number of intervals: 4000e (EC Test Certificate, according to OIML R60 (2000))

ELECTRONIC\MECHANICAL FEATURES

- Gas dischargers to protect against atmospheric discharges
- Double connector for load cells interconnection and weight indicator connection, without junction box.
- RS485 communication technology
- Rice Lake communication protocol
- Power Supply: 8...15 Vdc
- Rated digital output: 60000 d
- Current consumption: 35 mA
- Internal resolution: 24 bit
- Converter rate: max. 40 conv./sec.
- RS485 communication speed: Max 100kHz.
- Operating temperature: -20 ~ +70 °C
- Compensated temperature: -10 ~ +40 °C
- Safe load limit: 120% F.S.
- Ultimate overload: 150% F.S.
- IP68 protection degree
- Stainless steel body
- 4-core RS485 cable as optional
- Nickel plated steel cable gland
- Self-centring spherical bases
- Equipped with anti-rotation system, to be combined with 173793 cups for proper operation

• CONNECTION

CABLE COLOR CODE	
RED	EXCITATION +
BLACK	EXCITATION -
GREEN	A+
WHITE	B-
METAL	Shield

VERSIONS

Available versions

Codice	Max (kg)
195843	30 000
195844	40 000



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano - Modena - Italy
Tel. +39.0536 843418

CHING-HWA SCALE AND WEIGHING SYSTEMS LTD

31-3, LN 26, FUXING RD. 710-YONGKANG DIST - 710 - TAINAN CITY - TAIWAN

Tel. 00886-6-2058115 Fax. 00886-6-2054915

armor@www.ching-hwa.com.tw

SALES AND TECHNICAL ASSISTANCE SERVICE